

QUIZ NO: 810
TOPIC: BUILDING MATERIALS AND CONSTRUCTION
DATE: 26/03/2024

1. The hardest rock is?

- [A] Marble
- [B] Diamond
- [C] Talc
- [D] Quartz

Answer: B

2. Bulking of sand is caused due to?

- [A] Surface moisture
- [B] Air voids
- [C] Viscosity
- [D] Clay contents

Answer: A

3. What does grade 33 cement indicate?

- [A] Tensile strength of 33 kN/m²
- [B] Tensile strength of 33 N/mm²
- [C] Compressive strength of 33 kN/m²
- [D] Compressive strength of 33 N/mm²

Answer: D

4. Grade 43 OPC shall be rejected if it remains in bulk storage in the factory for?

- [A] More than 3 months
- [B] More than 1 month
- [C] More than 6 months
- [D] More than 4 months

Answer: C

5. How much maximum percentage by mass of performance improvers can be added in grade 33?

- [A] 0.5
- [B] 1
- [C] 5
- [D] 0.1

Answer: C

6. In plastering, the 1st coat is called _____ and its thickness should be _____ mm?

- [A] Undercoat, 6-9
- [B] Floating coat, 6-9
- [C] Floating coat, 10-15
- [D] Undercoat, 10-15

Answer: D

7. In a lime-cement plaster, ratio 1:1:6 corresponds to?

- [A] Lime: cement: sand
- [B] Cement: Lime: sand
- [C] Lime: sand: gravel
- [D] Cement: sand: gravel

Answer: B

8. Which of the below is not a plaster finish?

- [A] Rough cast
- [B] Pebble dash
- [C] Sand faced
- [D] Wooden

Answer: D

9. Anticorrosive paint is _____ in colour?

- [A] Black
- [B] Blue
- [C] White
- [D] Yellow

Answer: A

10. Spray painting is used to?

- [A] Get textured paint
- [B] Reach high areas
- [C] Apply large amount of paint
- [D] Apply paint without touching surface

Answer: D

Join our social media platforms

